



VEHICLE SCRUTINY CHECK LIST

A vehicle will not be allowed to start unless it conforms to the safety requirements detailed below

- Minimum 3-point Seat belts as provided by the manufacturer are mandatory.
- Tyres must be in good condition, with no cord or belts showing or cracks in the tread or sidewall.
- Throttle return action shall be safe and positive.
- No excessive fuel, oil, water or brake fluid leaks should be observed when the engine is running.
- Steering “spinner” knobs shall not be permitted and mechanical components like wheel bearings, shocks, steering and suspension shall be in good operating condition.
- Pedal operation must not be impeded. Driver’s side floor mat must be removed unless securely mounted. OE fasteners designed to prevent the mat from moving forward satisfy this requirement if they are in good working order.
- Wheels must be safely affixed. They shall not be reversed so that the lughole taper does not mate with the chamfer of the lugs. All studs and lug nuts must be present and functional.
- Vehicles must have a means of access on either side of the Passenger compartment which can be operated from inside or outside. Access must be sufficient to remove an occupant without interference from any door locking devices
- Vehicles participating in Modified and Open Group classes must be equipped with at least one fire extinguisher of 2 Kgs (Dry Power), securely mounted within easy access of the driver.
- Vehicles participating in the Open Group must be equipped with 4-point seat harness. It is NOT permitted to install an auxiliary fuel tank.

In addition to above, the following are additional requirements:

HIGHLIGHTED IS COMPULSORY FOR RALLY PREP		
Sr. No.	Particulars	Description
1	Hardtop/ Rally Cabin	Hard top is Mandatory
2	Roll Cage	Specified to Appendix J of the FMSCI Tech Regs.
3	Safety Harness	FIA approved 4 point harness
4	Helmets	Conforming to FIA regulations
5	Seats	FIA Approved Rally seats for Driver
6	Circuit Breaker	Mandatory for Rally Prep Class
7	Underbody Protection	Recommended - Should be under the oil sump
8	Tyre tread depth	Should be in good condition having a minimum tread depth of 4mm at least, sidewalls should not be damaged
9	Towing eye Front/ Rear	Towing eye should be painted red. If of the removable screw-on

		type, should be carried for inspection during scrutiny.
10	Horn	Working Horn Required
11	Head Lights	Functional in High Beam/ dipper mode; bulbs should be of twin filament type
12	Parking Lights	Fully Functional
13	Brake Lights	Fully Functional
14	Side Indicators	Fully Functional
15	Reverse Lights	Fully Functional
16	Number Plate Lights	Fully Functional
17	Extra Lighting	Mandatory for Rally Prep Classes running night track Should not be mounted above the lower level of the front windscreen and must be in pairs.
18	Identity Card	Attached to a lanyard must be worn around the neck.
19	Rally Insurance (COMPULSORY)	High Risk PA insurance of 5lac each for Driver Special Rally cover for the competing vehicle
20	Rear view Mirrors	1 each on the driver and co-driver side mounted on the doors and one inside the cabin for the driver
21	Display of Names & Blood Groups	Must for all crew members, to be displayed on black background of 4in. X 8in. dimension. with white letters & symbols.
22	Competition Number	Displayed as per SR
23	Compulsory Ads	Displayed as per SR